

QTICKET

SMART TICKETING TERMINAL FOR LEISURE APPLICATIONS



Ticketing terminal designed for leisure applications such as stadiums, amusement parks, water parks, and fitness & wellness centers.

cominfo

By **GUNNEBO** Entrance Control

QTICKET

SMART TICKETING TERMINAL FOR LEISURE APPLICATIONS

IDENTIFICATION OPTIONS

Adjustable to meet various security standards. QTicket supports multiple identification methods, such as QR codes, contactless cards, wristbands, and face recognition.

OFFLINE MODE

Operational in offline mode (either as a default setting or in case of a network outage). All records are saved in internal memory – no data ever gets lost.



QR CODE



CONTACTLESS CARD



WRISTBAND



FACE RECOGNITION

APPLICATION AREAS



STADIUMS &
SPORT FACILITIES



WATER PARKS &
LEISURE CENTERS



FITNESS &
GYMS

EASY & INTUITIVE USE

QTicket is designed with the user in mind, making it convenient to use. With intuitive graphics, the user will always know where to place the event tickets. The 7" screen features high contrast, ensuring good readability even in direct sunlight.

supports multiple languages (UTF-8)
illuminated area shows where to place QR codes





BENEFITS OF QTICKET

- speedy verification with numerous identification options
- durable plastic housing & tempered glass
- can be installed onto speed gates/turnstiles (on a bracket)
- supports bi-directional passage
- seamless connectivity with WSS WebAPI protocol
- indoor & outdoor use
- anti-passback feature (online mode)
- energy-efficient thanks to stand-by mode
- RGB signal light with 360-degree visibility
- local authorization even during temporary network (Ethernet) outages, based on a pre-synchronized database

TECHNICAL PARAMETERS

Dimensions	149 × 296,4 × 45,6 mm (W × H × D) 5,87" × 11,67" × 1,80"
Operating Environment	Indoor / Outdoor -20°C – 55°C (-4°F – 131°F) With face recognition 0°C – 50°C (32°F – 122°F) IP65
Power Supply	12 – 36 VDC or PoE (Power over Ethernet)
Power Consumption	0,8 A (12 VDC) / 9,6 W, Power Save Mode Available
Housing	PC ABS with Tempered Glass
Supported RFID	RFID Cards & Wristbands at 13.56 MHz ISO 14443A, ISO 14443B, ISO 15639 E.g. Mifare Classic, Mifare DESFire, Mifare Ultralight, TagIt HFI, EM 4035, EM 4135 RFID Cards & Wristbands at 125 kHz E.g. HID, HITAG1, HITAG2, EM 4102, Cassi-Rusco
Supported Barcode Types	Barcode tickets 1D and 2D barcodes tickets (including QR code) Mobile tickets 1D and 2D barcodes received by mobile phones (including QR code) Print@Home tickets Tickets printed at home on A4 size paper
Display Type	Full-colour graphic display covered with tempered glass, capacitive touch (optional) Sun-readable 7" LCD display, resolution 800 × 480
Inputs / Outputs	4/4 (optionally 8/8) (Galvanically isolated input signals / potential free outputs)
Communication Interface	Ethernet (10/100 Mbps)
Software Integration	WSS WebAPI protocol for integration with access control or ticketing system online mode offline mode
Internal Memory	up to 160 000 card users up to 100 000 transactions
Turnstile / Gate Control	One way mode Bi-directional mode by one Ticket terminal (using external RFID readers)
Installation	wall-mounted or pole-mounted (optional)

cominfo

By **GUNNEBO** Entrance Control

COMINFO, a.s. | Nabrezi 695, 760 01 Zlín-Prstne, Czech Republic | +420 603 151 333 | cominfo@cominfo.cz